

Safety Data Sheet (SDS)OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS
Rev03.

Printing date 06/13/2013

Reviewed on 06/13/2013

1 Product and Company Identification

- **Product identifier**
- **Trade name: Tire Sealant**
- **Article number:** Marath TireSeal
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Product description**
This tire sealant is inserted into the tube prior to tube inflation and is used to seal tire punctures.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Marathon Industries
7925 South 196th Street
Kent, WA 98032 USA
Ph: 253-893-7014
Fax: 253-893-7021
- **Emergency telephone number:** Chemtrec 800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS07

H302 Harmful if swallowed.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard-determining components of labeling:**
ethylene glycol
- **Hazard statements**
H302 Harmful if swallowed.
- **Precautionary statements**
Precautionary statements
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P330 Rinse mouth.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Classification system:** NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS
Rev03.

Printing date 06/13/2013

Reviewed on 06/13/2013

Trade name: Tire Sealant

(Contd. of page 1)

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

| | |
|---|--------|
| Crumb Rubber | 2-12% |
| water, distilled water, deionized water | 40-60% |

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

| | | | |
|--------------------------------|-----------------|--------|--------|
| · Dangerous components: | | | |
| 107-21-1 | ethylene glycol | ⚠ H302 | 25-50% |
| 9004-34-6 | Cellulose | | ≤ 2.5% |

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
If skin irritation continues, consult a doctor.
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Immediately call a doctor.
Do not induce vomiting; immediately call for medical help.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Information for doctor:** Treat symptomatically and supportively. No specific antidote.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS
Rev03.

Printing date 06/13/2013

Reviewed on 06/13/2013

Trade name: Tire Sealant

(Contd. of page 2)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.
- **Additional information** May be combustible at high temperature.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

107-21-1 ethylene glycol

| | |
|-----|---|
| TLV | Short-term value: C 100 mg/m ³ |
| | H |

9004-34-6 Cellulose

| | |
|-----|---|
| PEL | Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction |
| REL | Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction |
| TLV | Long-term value: 10 mg/m ³ |

- **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 4)

Safety Data Sheet (SDS)OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS
Rev03.

Printing date 06/13/2013

Reviewed on 06/13/2013

Trade name: Tire Sealant

(Contd. of page 3)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
 - Form:** Liquid
 - Color:** Various colors
- **Odor:** Slight
- **Odour threshold:** Not determined.
- **pH-value:** 8.25
- **Change in condition**
 - Melting point/Melting range:** -38 °C (-36 °F)
 - Boiling point/Boiling range:** 100 °C (212 °F)
- **Flash point:** 111 °C (232 °F)
- **Flammability (solid, gaseous):** Not applicable.
- **Ignition temperature:** 410 °C (770 °F)
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not selfigniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**
 - Lower:** 0.0 Vol %
 - Upper:** 53.0 Vol %

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS
Rev03.

Printing date 06/13/2013

Reviewed on 06/13/2013

Trade name: Tire Sealant

(Contd. of page 4)

- **Vapor pressure @ 38 °C (100 °F):** 107 hPa (80 mm Hg)
- **Density @ 20 °C (68 °F):** 1.08 g/cm³ (9.013 lbs/gal)
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with Water:** Partly soluble.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
 - Organic solvents:** 0.0 %
 - Water:** 53.2 %
 - VOC content:** 44.9 %
- **Solids content:** 1.9 %
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Product is stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Strong oxidizing agents.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

| | | |
|---|------|---------------------|
| · LD/LC50 values that are relevant for classification: | | |
| 107-21-1 ethylene glycol | | |
| Oral | LD50 | 5840 mg/kg (rat) |
| Dermal | LD50 | 9530 mg/kg (rabbit) |

- **Primary irritant effect:**
- **on the skin:** May be irritating.
- **on the eye:** May be irritating.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS
Rev03.

Printing date 06/13/2013

Reviewed on 06/13/2013

Trade name: Tire Sealant

(Contd. of page 5)

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Observe all federal, state and local environmental regulations when disposing of this material.

· **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

* 14 Transport information

· **UN-Number**

· **DOT, ADR, ADN, IMDG, IATA** Not regulated

· **UN proper shipping name** Not regulated

None

· **ADR, ADN, IMDG, IATA** Void

· **Transport hazard class(es)**

· **DOT, ADR, ADN, IMDG, IATA**

· **Class** Void

· **Packing group**

· **DOT, ADR, IMDG, IATA** Void

· **Environmental hazards:**

· **Marine pollutant:** No

· **Special precautions for user** Not applicable.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **UN "Model Regulation":** -

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS
Rev03.

Printing date 06/13/2013

Reviewed on 06/13/2013

Trade name: Tire Sealant

(Contd. of page 6)

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

| | |
|--|------------------------------------|
| Section 355 (extremely hazardous substances): | None of the ingredients is listed. |
|--|------------------------------------|

| | |
|--|--------------------------|
| Section 313 (Specific toxic chemical listings): | 107-21-1 ethylene glycol |
|--|--------------------------|

| | |
|---|---|
| TSCA (Toxic Substances Control Act): | 107-21-1 ethylene glycol |
| | 9004-34-6 Cellulose |
| | water, distilled water, deionized water |

- **Proposition 65**

| | |
|---|------------------------------------|
| Chemicals known to cause cancer: | None of the ingredients is listed. |
|---|------------------------------------|

| | |
|--|------------------------------------|
| Chemicals known to cause reproductive toxicity for females: | None of the ingredients is listed. |
|--|------------------------------------|

| | |
|--|------------------------------------|
| Chemicals known to cause reproductive toxicity for males: | None of the ingredients is listed. |
|--|------------------------------------|

| | |
|---|------------------------------------|
| Chemicals known to cause developmental toxicity: | None of the ingredients is listed. |
|---|------------------------------------|

- **Carcinogenic categories**

| | |
|--|------------------------------------|
| EPA (Environmental Protection Agency) | None of the ingredients is listed. |
|--|------------------------------------|

| | | |
|---|--------------------------|----|
| TLV (Threshold Limit Value established by ACGIH) | 107-21-1 ethylene glycol | A4 |
|---|--------------------------|----|

| | |
|---|------------------------------------|
| NIOSH-Ca (National Institute for Occupational Safety and Health) | None of the ingredients is listed. |
|---|------------------------------------|

| | |
|--|------------------------------------|
| OSHA-Ca (Occupational Safety & Health Administration) | None of the ingredients is listed. |
|--|------------------------------------|

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07

- **Signal word** Warning

- **Hazard-determining components of labeling:**

ethylene glycol

(Contd. on page 8)

Safety Data Sheet (SDS)OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS
Rev03.

Printing date 06/13/2013

Reviewed on 06/13/2013

Trade name: Tire Sealant

(Contd. of page 7)

• Hazard statements

H302 Harmful if swallowed.

• Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P264 Wash thoroughly after handling.
- P270 Do no eat, drink or smoke when using this product.
- P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
- P330 Rinse mouth.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Abbreviations and acronyms:

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent

• * Data compared to the previous version altered.SDS / MSDS Created by MSDS Authoring Services (www.MSDSAuthoring.com)